




Switching Diodes

FEATURES

- Fast Switching Speed
- Surface mount package ideally Suited for Automatic Insertio
- High Conductance
- Qualified to AEC-Q101 Standards for High Reliability




BAV23A

BAV23C

BAV23S

PINNING

PIN	DESCRIPTION
a	Cathode
b	Anode



Maximum Ratings @Ta=25°C

Parameter	Symbol	Value	Unit
Repetitive peak reverse voltage	V_{RRM}	250	V
Average rectified output current	I_o	200	mA
Non-Repetitive Peak Forward Surge Current @t=8.3ms	I_{FSM}	1.0	A
Power dissipation	P_D	350	mW
Thermal resistance junction to ambient	R_{thJA}	357	°C/W
Junction temperature	T_J	150	°C
Storage temperature range	T_{STG}	-55 ~ +150	°C

Electrical Characteristics @Ta=25°C

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse breakdown voltage	V_{BR}	$I_R=100\mu A$	250			V
Reverse voltage leakage current	I_R	$V_R=200V$			0.1	μA
Forward voltage	V_F	$I_F=100mA$ $I_F=200mA$			1.0 1.25	V
Diode capacitance	C_D	$V_R=0V, f=1MHz$		5		pF
Reveres recovery time	t_{rr}	$I_F=I_R=30mA, V_R=6V$ $I_{rr}=3mA, R_L=100\Omega$			50	ns



Fig.1 Power Derating Curve




Fig.2 Reverse Characteristics




Fig.3 Forward Characteristics






Fig.4 Capacitance Characteristics






SOT-23 Package Outline Dimensions



The recommended mounting pad size



Marking

Type number	Marking code
BAV23A	KT7
BAV23C	KT6
BAV23S	KT8



Important Notice and Disclaimer

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice.

Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Jingdao Microelectronics assume any liability for application assistance or customer product design.

Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.